Quassel IRC - Bug #322

"quasselcore -h|--help" tries to start quasselcore instead of just displaying the help message

09/21/2008 11:37 PM - billie

Status: Resolved Start date:

Priority: High Due date:

Assignee: Sputnick % Done: 0%

Category: Quassel Core Estimated time: 0.00 hour

Target version: 0.3.1

Version: 0.13.1 **OS:** Any

Description

The following is displayed after the help message.

quasselcore --help

2008-09-21 23:22:53 Info: Storage Backend is ready. Quassel Schema Version: 11

2008-09-21 23:22:53 Error: Could not open GUI client port 4242: The bound address is already in use

Just out of curiosity I tried to use a port which is not already used and I got the following.

quasselcore --port=3000 --help

2008-09-21 23:30:51 Info: Storage Backend is ready. Quassel Schema Version: 11

2008-09-21 23:30:51 Info: Listening for GUI clients on IPv6 port 3000 using protocol version 5

The strange thing is I can not find an additional process of quasselcore running at port 3000. So it is not really starting or dies immediately after issuing the command.

Associated revisions

Revision 0f4d21d538c8cb4c8fb12cd285c4d7556714c2f3 - 09/22/2008 05:40 PM - Manuel Nickschas

Don't start a core in CoreApplication's dtor... fixes BR #322

Revision 0f4d21d5 - 09/22/2008 05:40 PM - Manuel Nickschas

Don't start a core in CoreApplication's dtor... fixes BR #322

History

#1 - 09/22/2008 05:41 PM - Sputnick

 $\underline{\text{http://git.quassel-irc.org/?p=quassel.git:a=commit:h=0f4d21d538c8cb4c8fb12cd285c4d7556714c2f3}}$

04/10/2024 1/1