Quassel IRC - Bug #99

Kick reason is not sent correctly

02/12/2008 06:09 PM - Sputnick

Status:	Closed	**Start date:**	
Priority:	High	**Due date:**	
Assignee:	Sputnick	**% Done:**	0%
Category:	Quassel Core	**Estimated time:**	0.00 hour
Target version:	0.2.0-alpha1		
Version:	0.13.1	**OS:**	Any

Description

/kick This is a long kick message

This results in the kick reason being "message" only. Probably something about the parameter handling in the kick user handler.

Associated revisions

Revision 6bff16ce4afeea153ffaf3d1916b6ba977853a27 - 02/13/2008 03:46 AM - Manuel Nickschas

Encodings are now honored for both sending and receiving. Cleaned up encode/decode
stuff in the handlers and switched putCmd() et. al. to accepting (encoded) QByteArray only instead
of QString.
Also fixed notices being shown in a separate buffer upon reconnect, and the kick message problem (BR #99).
Oh, and the default kick reason defined in your identity is used if appropriate now.

Revision 6bff16ce - 02/13/2008 03:46 AM - Manuel Nickschas

Encodings are now honored for both sending and receiving. Cleaned up encode/decode
stuff in the handlers and switched putCmd() et. al. to accepting (encoded) QByteArray only instead
of QString.
Also fixed notices being shown in a separate buffer upon reconnect, and the kick message problem (BR #99).
Oh, and the default kick reason defined in your identity is used if appropriate now.

History

#1 - 02/13/2008 03:47 AM - Sputnick

Fixed.