

## Quassel IRC - Bug #103

### Treat global messages correctly

02/14/2008 12:04 PM - EgS

<b>Status:</b>	Closed	<b>Start date:</b>	
<b>Priority:</b>	High	<b>Due date:</b>	
<b>Assignee:</b>	EgS	<b>% Done:</b>	0%
<b>Category:</b>	Quassel Core	<b>Estimated time:</b>	0.00 hour
<b>Target version:</b>	0.2.0-alpha1	<b>OS:</b>	Any
<b>Version:</b>	0.13.1		
<b>Description</b>			
They seem to be correctly recognized as a Querytype but the sender is not set correctly. (i.e.: \$*)			
<b>Additional information:</b>			
3.3.1 Private messages			
Command: PRIVMSG			
Parameters: <msgtarget> <text to be sent>			
PRIVMSG is used to send private messages between users, as well as to send messages to channels. <msgtarget> is usually the nickname of the recipient of the message, or a channel name.			
The <msgtarget> parameter may also be a host mask (#<mask>) or server mask (\$<mask>). In both cases the server will only send the PRIVMSG to those who have a server or host matching the mask. The mask MUST have at least 1 (one) "." in it and no wildcards following the last ".". This requirement exists to prevent people sending messages to "*" or "\$*", which would broadcast to all users. Wildcards are the '*' and '?' characters. This extension to the PRIVMSG command is only available to operators.			