

Quassel IRC - Feature #713

Generating away-nicks and/or disconnected-nicks "on the fly"

06/02/2009 09:01 PM - valual

Status:	New	Start date:	06/02/2009
Priority:	Normal	Due date:	
Assignee:		% Done:	0%
Category:	General / Unspecified	Estimated time:	0.00 hour
Target version:			
OS:	Any		
Description			
<p>I'd like to see a feature introduced, that lets you use some variables in the Away-Nick and/or Disconnected-Nick settings.</p> <p>For example:</p> <p>\$NICK = Current Nick Example: kageookami \$IDENTITY.NICK = (1st) Nick of the choosen Identity (or as an array?) Example: kage-ookami</p> <p>so you can set your away nick to:</p> <p>`\${NICK}[afk] results in kageookami[afk] or for the disconnected nick:</p> <p>`\${IDENTITY.NICK}[discon] results in kage-ookami[discon]</p> <p>I've taken bash-style variables to make the point, not sure what style of substitution would work best. Some other possibilities would be VARNAME or simple %a %c %n stuff...</p> <p>This could also be introduced as a plugin (script?) but would need some event handlers introduced (more than a simple /exec command can)...</p> <p>MaxNickLen provided by the irc server should be taken into consideration here. (how do we handle results that are too long? truncate the variable part, or the result? <i>needs to be discussed</i></p>			